

# SEMI-FIT BARRELS FOR GLOCK - Semi Fit 9mm Barrel for Glock 19

These barrels for Glock are "Semi Fit", meaning they general require little to no fitting. Barrels may drop-in, but expect some fitting to be necessary. Barrels are stock length for the designated Glock. Bar-Sto Precision Machine has been making some of the finest auto-pistol barrels since 1971. Bar-Sto barrels have been used by the U.S. Marine Corps Marksman Unit since 1977. All Bar-Sto Pistol barrels are machined from solid 416 stainless steel bar stock which has been heat treated 39 to 43 RC and 180,000 PSI tensile strength. Barrels are machined, bored, and rifled completely in Bar-Sto's own shop. All barrels have a rate of twist of 1 turn in 16".



## Attributes

- Name: [Semi Fit 9mm Barrel for Glock 19](#)
- Manufacturer: [BAR-STO PRECISION MACHINE](#)
- Product no.: 100015627
- Mfr. No.:
- Cartridge: 9 mm Luger
- Finish: Stainless Steel
- Make: Glock
- Model: 19
- Delivery weight: 0.041kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 229mm

## Item details

Made in USA

US export classification: 0A501.c

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for SEMIFIT BARRELS FOR GLOCK](#)
- [About Us](#)

# Safety Instruction Guide for SEMIFIT BARRELS FOR GLOCK

## Introduction

Thank you for choosing the SEMIFIT BARRELS FOR GLOCK. This guide provides essential safety instructions and information to ensure the safe use and handling of your new barrel. Please read this guide carefully before installation and use.

## General Safety Guidelines

- Ensure that the barrel is compatible with your Glock model before installation.
- Always handle firearms and accessories with care and follow all safety practices.
- Store the barrel in a secure location, away from children and unauthorized users.
- Regularly inspect the barrel for any signs of wear or damage.
- Report any unsafe conditions or incidents to the appropriate authorities.

## Specific Safety Precautions for Use

- Always wear appropriate safety gear, including eye and ear protection, when handling firearms.
- Do not use the barrel if it shows signs of damage or excessive wear.
- Ensure the firearm is unloaded before installing or removing the barrel.
- Follow the manufacturer's instructions for installation and maintenance.
- Be aware of the legal requirements for firearm modifications in your area.

## Instructions for Installation and Usage

### 1. Preparation

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools for installation, including a cleaning kit and appropriate wrenches.

### 2. Installation

- Remove the existing barrel from the Glock by following the manufacturer's instructions.
- Carefully insert the SEMIFIT BARREL into the slide of the Glock.
- Check for proper alignment and fit. Some minor fitting may be necessary.
- Secure the barrel according to the manufacturer's specifications.

### 3. Usage

- After installation, conduct a function check to ensure proper operation.
- Always follow safe handling practices while using the firearm.
- Regularly clean and maintain the barrel to ensure optimal performance.

## Disposal Instructions

- Dispose of the barrel in accordance with local regulations regarding firearm components.
- Do not discard in regular household waste.
- Contact local waste management authorities for proper disposal methods.

## **Contact Information for Further Support**

For any safety inquiries or additional information regarding the SEMIFIT BARRELS FOR GLOCK, please refer to the manufacturer's contact details provided in the product packaging or visit their official website.

## **Conclusion**

By following these safety instructions, you can help ensure a safe and enjoyable experience with your SEMIFIT BARRELS FOR GLOCK. Always prioritize safety and adhere to best practices when handling firearms and accessories.

# About Us

## Brownells Austria

**Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

[www.brownells.at](http://www.brownells.at)