

BEARING DELAY 9MM LUGER COMPLETE UPPER RECEIVER - BEARING DELAY 9MM LUGER 4.5" BBL ASSEMBLED UPPER RECEIVER

The Bearing Delay Upper Receiver is a complete upper receiver system ready to be paired with the AR lower receiver of your choice. Available in 5 different barrel lengths: 4.5", 7.5", 11", 14.5", 16" - all threaded for a 1/2-28 muzzle device. No 9mm-specific buffer needed. The Bearing Delay Upper Receiver is designed to work with standard AR-15 buffers. The heart of the Bearing Delay Upper Receiver is the unique ball bearing bolt carrier group (BCG). The ball bearings interface with corresponding features in the barrel extension and provide the lockup in battery and the delay after firing. The system can be tuned by replacing the Lifter to change the angle of the surfaces that push the bearings from the inside of the BCG. The bolt face includes our unique center ejector to provide the most consistent ejection of any 9mm AR on the market. The firing pin passes through the ejector. Take all the benefits of roller delay: reliability, durability, low recoil and combine with the familiarity of the AR-15 platform. Rollers are obsolete. Each of Mean's ball bearings has the same contact surface area of the original MP5 roller. So with their 3 bearings, they have 50% more contact surface area than a traditional roller delay. This means that even with the higher pressures of modern ammunition, the Bearing Delay system has greater durability than any roller delay. The ability to tune the system by swapping the Lifter means that the Bearing Delay™ system can be tuned based on ammunition type, barrel length, suppressor, or any other factor. Each Bearing Delay Upper Receiver includes two Lifters. If you elect to use MEAN Arms Endomags (Ejectorless), the Bearing Delay Upper Receiver is compatible with milspec lower receivers OR you can use dedicated pistol magazine lower receivers. Most pistol magazine lower receivers will need to have the stationary ejector removed to be compatible with the Bearing Delay system. Each Bearing Delay Upper Receiver includes 2 Ejectorless Endomags. MA Upper Receiver The Bearing Delay Upper Receiver includes a slick side billet machined aluminum upper receiver that adheres to milspec standards. No forward assist. MA Handguard The new MA Handguard is a free float hybrid design including a very rigid high temperature and high strength polymer body with a metallic insert that is overmolded (permanently attached) within the handguard and threads onto the specially designed barrel nut. Internal width (flat to flat): ~1.375" Available in 5 lengths based on the barrel configurations of the Bearing Delay Upper Receiver. MA Charging Handle The MA Charging Handle is a new ambidextrous design incorporating both steel and aluminum machined components. MA Muzzle Device The MA Muzzle Device reduces recoil and muzzle flash. Comes with a left-hand threaded jam nut which eliminates the need for a crush washer. SPECS Caliber: 9×19mm Parabellum Compatible with both milspec AR-15 and dedicated pistol-magazine lower receivers Works with standard AR-15 buffers 5 available barrel lengths: 4.5", 7.5", 11", 14.5" and 16" Weight of entire Upper (BCG alone is just under 11oz) 4.5" is 2.59 lbs 7.5" is 2.92 lbs 11" is 3.23 lbs 14.5" is 3.57 lbs 16" is 3.72 lbs Each Bearing Delay Upper Receiver includes: Fully tunable ball bearing bolt carrier group MA Upper Receiver - slick side billet machined aluminum upper receiver MA Handguard - free float hybrid metal/polymer design MA Charging Handle - new ambidextrous design MA Muzzle Device - exclusive machined design reduces recoil and muzzle flash Also included with the purchase of the Bearing Delay Upper Receiver: 1 additional Lifter for tuning the system (2 total included) 2 Ejectorless EndoMags (PMAGs NOT included)



Attributes

- Name: BEARING DELAY 9MM LUGER 4.5" BBL ASSEMBLED UPPER RECEIVER
- Manufacturer: MEAN ARMS
- Product no.: 430109847
- Mfr. No.: 2101669
- Cartridge: 9 mm Luger
- Color: Black
- Finish: Matte
- Length: 4.5"
- Make: AR-15
- Muzzle: 1/2-28
- Style: Complete
- Delivery weight: 1.361kg
- UPC: 855926007141

Item details

Made in USA

This product is excluded from discount promotions.

US export classification: I(g)

Table of Contents

- [Startpage](#)
- [Deutsch: Sicherheitshinweise für den Bearing Delay 9mm Luger Complete Upper Receiver](#)
- [English: Safety Instruction Guide for Bearing Delay 9mm Luger Complete Upper Receiver](#)

Sicherheitshinweise für den Bearing Delay 9mm Luger Complete Upper Receiver

Einleitung

Herzlichen Glückwunsch zu Ihrem Kauf des Bearing Delay 9mm Luger Complete Upper Receiver von MEAN ARMS. Dieses Produkt wurde entwickelt, um Ihnen eine zuverlässige und leistungsstarke Lösung für Ihre AR15-Plattform zu bieten. Um die Sicherheit und optimale Nutzung zu gewährleisten, lesen Sie bitte diese Sicherheitshinweise sorgfältig durch.

Allgemeine Sicherheitshinweise

- Verwenden Sie das Produkt ausschließlich gemäß den Anweisungen in diesem Handbuch.
- Überprüfen Sie vor der Verwendung, ob alle Komponenten vollständig und unbeschädigt sind.
- Halten Sie das Produkt von Kindern und unerfahrenen Benutzern fern.
- Tragen Sie immer geeignete Schutzausrüstung, wie z.B. Schutzbrille und Gehörschutz, während der Nutzung.
- Achten Sie darauf, dass Sie in einem sicheren und genehmigten Bereich schießen.
- Informieren Sie sich über lokale Gesetze und Vorschriften zum Schusswaffengebrauch.

Besondere Sicherheitsvorkehrungen bei der Verwendung

- Stellen Sie sicher, dass das Produkt vor der Verwendung korrekt installiert ist.
- Verwenden Sie nur die empfohlenen Munitionsarten, um eine sichere und zuverlässige Funktion zu gewährleisten.
- Überprüfen Sie regelmäßig den Zustand der Kugelgelagerten Bolt Carrier Group (BCG) und anderer beweglicher Teile.
- Achten Sie darauf, dass der Ausstoßer bei der Verwendung mit Pistolen-Laternen entfernt wird, um eine ordnungsgemäße Funktion zu gewährleisten.
- Bei Anzeichen von Beschädigungen oder Fehlfunktionen, verwenden Sie das Produkt nicht und wenden Sie sich an den Hersteller.

Anweisungen zur Installation und Nutzung

1. Installation des Upper Receivers

- Entfernen Sie den bestehenden Upper Receiver von Ihrem AR-Lower.
- Setzen Sie den Bearing Delay Upper Receiver auf das AR-Lower und stellen Sie sicher, dass er sicher einrastet.
- Überprüfen Sie, ob der Verschluss in der Batterieposition ist.

2. Verwendung des Produkts

- Laden Sie das Magazin mit der empfohlenen Munition.
- Stellen Sie sicher, dass der Abzug in der sicheren Position ist, bevor Sie das Magazin einsetzen.
- Nehmen Sie eine sichere Schussposition ein und überprüfen Sie Ihre Umgebung.
- Drücken Sie den Abzug, um zu schießen. Achten Sie darauf, dass Sie bei jedem Schuss die Waffe kontrollieren.

3. Feinabstimmung des Systems

- Um das System an verschiedene Munitionsarten oder Lauflängen anzupassen, können Sie den Lifter austauschen.
- Beachten Sie die Anweisungen zur Anpassung des Lifters, um die Funktionalität zu optimieren.

Entsorgungsanweisungen

- Entsorgen Sie alle Verpackungsmaterialien gemäß den örtlichen Vorschriften für Abfallentsorgung.
- Bei der Entsorgung von gebrauchten oder beschädigten Komponenten beachten Sie bitte die geltenden Gesetze und Vorschriften.
- Stellen Sie sicher, dass alle Teile, die nicht mehr verwendet werden, sicher und umweltgerecht entsorgt werden.

Kontaktinformationen für weitere Unterstützung

Für Fragen oder Unterstützung bezüglich des Bearing Delay 9mm Luger Complete Upper Receiver wenden Sie sich bitte an den Hersteller oder den Händler, bei dem Sie das Produkt erworben haben. Es ist wichtig, dass Sie bei Fragen zur Sicherheit oder zur Verwendung immer die richtige Unterstützung suchen.

Bitte beachten Sie, dass diese Sicherheitshinweise die grundlegenden Anforderungen der EUVerordnung über die allgemeine Produktsicherheit (GPSR) erfüllen. Sie sind dafür gedacht, Ihnen eine sichere und effektive Nutzung Ihres neuen Produkts zu ermöglichen.

Safety Instruction Guide for Bearing Delay 9mm Luger Complete Upper Receiver

Introduction

Thank you for choosing the Bearing Delay 9mm Luger Complete Upper Receiver. This product is designed for use with AR lower receivers and provides a unique ball bearing system for enhanced performance. Please read this safety instruction guide carefully to ensure safe and proper use of the product.

General Safety Guidelines

- Ensure that the product is used in accordance with all applicable laws and regulations.
- Always handle firearms and firearm components with care and respect.
- Keep the product out of reach of children and unauthorized persons.
- Inspect the upper receiver and its components regularly for any signs of wear or damage.
- Use only compatible ammunition as specified by the manufacturer.
- Follow all safety instructions provided by the manufacturer and any relevant authorities.

Specific Safety Precautions for Use

- **Firearm Safety:** Always treat the firearm as if it is loaded. Keep the muzzle pointed in a safe direction at all times.
- **Installation Caution:** Ensure that the upper receiver is properly installed on the lower receiver before use. Improper installation can lead to malfunction.
- **Ammunition Compatibility:** Use only 9mm Luger ammunition. Using incorrect ammunition can cause serious injury or damage to the firearm.
- **Buffer Compatibility:** This upper receiver is designed to work with standard AR15 buffers. Ensure that the buffer is compatible to avoid malfunctions.
- **Ejection Safety:** Be aware that the unique center ejector may affect how spent casings are ejected. Maintain a safe distance from the ejection port.

Instructions for Installation and Usage

1. Installation:

- Ensure that the AR lower receiver is unloaded and secure.
- Align the Bearing Delay Upper Receiver with the lower receiver.
- Secure the upper receiver to the lower receiver using the appropriate takedown pins.
- Confirm that the upper receiver is properly seated and locked in place.

2. Usage:

- Load the firearm only when you are ready to shoot.
- Always wear appropriate eye and ear protection when using the firearm.
- Fire the firearm in a safe and designated area.
- Follow the manufacturer's instructions for tuning the system using the Lifters provided.

Disposal Instructions

- Dispose of this product and any associated components in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Contact your local waste management authority for guidance on proper disposal methods.

Contact Information for Further Support

For any safety inquiries or concerns regarding the Bearing Delay 9mm Luger Complete Upper Receiver, please refer to the manufacturer's website or contact their customer support service.