

BEARING DELAY 9MM LUGER COMPLETE UPPER RECEIVER - BEARING DELAY 9MM LUGER 7.5" BBL ASSEMBLED UPPER RECEIVER

[Rifle Parts](#) > [Receiver Parts](#) > [Receivers](#) > [Upper Receivers](#)

The Bearing Delay Upper Receiver is a complete upper receiver system ready to be paired with the AR lower receiver of your choice. Available in 5 different barrel lengths: 4.5", 7.5", 11", 14.5", 16" - all threaded for a 1/2-28 muzzle device. No 9mm-specific buffer needed. The Bearing Delay Upper Receiver is designed to work with standard AR-15 buffers. The heart of the Bearing Delay Upper Receiver is the unique ball bearing bolt carrier group (BCG). The ball bearings interface with corresponding features in the barrel extension and provide the lockup in battery and the delay after firing. The system can be tuned by replacing the Lifter to change the angle of the surfaces that push the bearings from the inside of the BCG. The bolt face includes our unique center ejector to provide the most consistent ejection of any 9mm AR on the market. The firing pin passes through the ejector. Take all the benefits of roller delay: reliability, durability, low recoil and combine with the familiarity of the AR-15 platform. Rollers are obsolete. Each of Mean's ball bearings has the same contact surface area of the original MP5 roller. So with their 3 bearings, they have 50% more contact surface area than a traditional roller delay. This means that even with the higher pressures of modern ammunition, the Bearing Delay system has greater durability than any roller delay. The ability to tune the system by swapping the Lifter means that the Bearing Delay™ system can be tuned based on ammunition type, barrel length, suppressor, or any other factor. Each Bearing Delay Upper Receiver includes two Lifters. If you elect to use MEAN Arms Endomags (Ejectorless), the Bearing Delay Upper Receiver is compatible with milspec lower receivers OR you can use dedicated pistol magazine lower receivers. Most pistol magazine lower receivers will need to have the stationary ejector removed to be compatible with the Bearing Delay system. Each Bearing Delay Upper Receiver includes 2 Ejectorless Endomags. MA Upper Receiver The Bearing Delay Upper Receiver includes a slick side billet machined aluminum upper receiver that adheres to milspec standards. No forward assist. MA Handguard The new MA Handguard is a free float hybrid design including a very rigid high temperature and high strength polymer body with a metallic insert that is overmolded (permanently attached) within the handguard and threads onto the specially designed barrel nut. Internal width (flat to flat): ~1.375" Available in 5 lengths based on the barrel configurations of the Bearing Delay Upper Receiver. MA Charging Handle The MA Charging Handle is a new ambidextrous design incorporating both steel and aluminum machined components. MA Muzzle Device The MA Muzzle Device reduces recoil and muzzle flash. Comes with a left-hand threaded jam nut which eliminates the need for a crush washer. SPECS Caliber: 9×19mm Parabellum Compatible with both milspec AR-15 and dedicated pistol-magazine lower receivers Works with standard AR-15 buffers 5 available barrel lengths: 4.5", 7.5", 11", 14.5" and 16" Weight of entire Upper (BCG alone is just under 11oz) 4.5" is 2.59 lbs 7.5" is 2.92 lbs 11" is 3.23 lbs 14.5" is 3.57 lbs 16" is 3.72 lbs Each Bearing Delay Upper Receiver includes: Fully tunable ball bearing bolt carrier group MA Upper Receiver - slick side billet machined aluminum upper receiver MA Handguard - free float hybrid metal/polymer design MA Charging Handle - new ambidextrous design MA Muzzle Device - exclusive machined design reduces recoil and muzzle flash Also included with the purchase of the Bearing Delay Upper Receiver: 1



additional Lifter for tuning the system (2 total included) 2 Ejectorless
EndoMags (PMAGs NOT included)

Attributes

- Name: [BEARING DELAY 9MM LUGER 7.5" BBL ASSEMBLED UPPER RECEIVER](#)
- Manufacturer: [MEAN ARMS](#)
- Product no.: 430109848
- Mfr. No.: 2101769
- Cartridge: 9 mm Luger
- Color: Black
- Finish: Matte
- Length: 7.5"
- Make: AR-15
- Muzzle: 1/2-28
- Style: Complete
- Delivery weight: 1.814kg
- UPC: 855926007158

Item details

Made in USA

This product is excluded from discount promotions.

US export classification: I(g)

Table of Contents

- Startpage
- Safety Instruction Guide for Bearing Delay 9mm Luger Complete Upper Receiver
- About Us

Safety Instruction Guide for Bearing Delay 9mm Luger Complete Upper Receiver

Introduction

Thank you for purchasing the Bearing Delay 9mm Luger Complete Upper Receiver. This guide provides essential safety instructions to ensure the safe use of the product. Please read this manual carefully before installation and usage. Adhering to these guidelines will help prevent accidents and ensure a safe shooting experience.

General Safety Guidelines

- Ensure that the product is used in accordance with the manufacturer's instructions.
- Always treat every firearm as if it is loaded.
- Keep the firearm pointed in a safe direction at all times.
- Store the product in a secure location, out of reach of children and unauthorized users.
- Regularly inspect the upper receiver and associated components for signs of wear or damage.
- Use only compatible ammunition as specified in the product description.
- Be aware of your surroundings and ensure a clear shooting area.
- Wear appropriate personal protective equipment, including eye and ear protection, when using the product.
- Report any unsafe product incidents or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the Bearing Delay Upper Receiver is installed on a compatible AR15 lower receiver.
- Do not attempt to modify the upper receiver or its components in any way.
- Follow all local laws and regulations regarding firearm use and ownership.
- Always check the chamber to ensure it is clear before handling or cleaning the firearm.
- When using suppressors or other muzzle devices, ensure they are properly installed and compatible with the upper receiver.
- Be cautious of the ejection path when firing to avoid injury from ejected casings.
- Do not use the upper receiver if it shows signs of damage or malfunction.

Instructions for Installation and Usage

1. Installation

- Ensure that you have a compatible AR15 lower receiver.
- Align the Bearing Delay Upper Receiver with the lower receiver.
- Secure the upper receiver to the lower receiver using the provided takedown pins.
- Check that the upper and lower receivers are properly seated and locked in place.

2. Usage

- Load the firearm with the appropriate ammunition.
- Ensure that the safety is engaged before loading.
- Once ready to fire, disengage the safety and aim at the target.
- Pull the trigger to fire. Be mindful of the ejection of spent casings.
- After firing, engage the safety and check the chamber before handling.

3. Maintenance

- Regularly clean the upper receiver and bolt carrier group to ensure optimal performance.

- Use appropriate cleaning supplies and follow the manufacturer's recommendations for maintenance.

Disposal Instructions

- Dispose of the upper receiver and any associated components in accordance with local regulations.
- Do not dispose of firearms or firearm components in regular household waste.
- Contact local authorities or waste management facilities for guidance on proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the Bearing Delay 9mm Luger Complete Upper Receiver, please refer to the manufacturer's website or customer service for assistance.

By following the safety instructions outlined in this guide, you can help ensure a safe and enjoyable experience with your Bearing Delay 9mm Luger Complete Upper Receiver. Always prioritize safety and stay informed about best practices in firearm handling.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at