

BEARING DELAY 9MM LUGER COMPLETE UPPER RECEIVER - BEARING DELAY 9MM LUGER 14.5" BBL ASSEMBLED UPPER RECEIVER

[Rifle Parts](#) > [Receiver Parts](#) > [Receivers](#) > [Upper Receivers](#)

The Bearing Delay Upper Receiver is a complete upper receiver system ready to be paired with the AR lower receiver of your choice. Available in 5 different barrel lengths: 4.5", 7.5", 11", 14.5", 16" - all threaded for a 1/2-28 muzzle device. No 9mm-specific buffer needed. The Bearing Delay Upper Receiver is designed to work with standard AR-15 buffers. The heart of the Bearing Delay Upper Receiver is the unique ball bearing bolt carrier group (BCG). The ball bearings interface with corresponding features in the barrel extension and provide the lockup in battery and the delay after firing. The system can be tuned by replacing the Lifter to change the angle of the surfaces that push the bearings from the inside of the BCG. The bolt face includes our unique center ejector to provide the most consistent ejection of any 9mm AR on the market. The firing pin passes through the ejector. Take all the benefits of roller delay: reliability, durability, low recoil and combine with the familiarity of the AR-15 platform. Rollers are obsolete. Each of Mean's ball bearings has the same contact surface area of the original MP5 roller. So with their 3 bearings, they have 50% more contact surface area than a traditional roller delay. This means that even with the higher pressures of modern ammunition, the Bearing Delay system has greater durability than any roller delay. The ability to tune the system by swapping the Lifter means that the Bearing Delay™ system can be tuned based on ammunition type, barrel length, suppressor, or any other factor. Each Bearing Delay Upper Receiver includes two Lifters. If you elect to use MEAN Arms Endomags (Ejectorless), the Bearing Delay Upper Receiver is compatible with milspec lower receivers OR you can use dedicated pistol magazine lower receivers. Most pistol magazine lower receivers will need to have the stationary ejector removed to be compatible with the Bearing Delay system. Each Bearing Delay Upper Receiver includes 2 Ejectorless Endomags. MA Upper Receiver The Bearing Delay Upper Receiver includes a slick side billet machined aluminum upper receiver that adheres to milspec standards. No forward assist. MA Handguard The new MA Handguard is a free float hybrid design including a very rigid high temperature and high strength polymer body with a metallic insert that is overmolded (permanently attached) within the handguard and threads onto the specially designed barrel nut. Internal width (flat to flat): ~1.375" Available in 5 lengths based on the barrel configurations of the Bearing Delay Upper Receiver. MA Charging Handle The MA Charging Handle is a new ambidextrous design incorporating both steel and aluminum machined components. MA Muzzle Device The MA Muzzle Device reduces recoil and muzzle flash. Comes with a left-hand threaded jam nut which eliminates the need for a crush washer. SPECS Caliber: 9×19mm Parabellum Compatible with both milspec AR-15 and dedicated pistol-magazine lower receivers Works with standard AR-15 buffers 5 available barrel lengths: 4.5", 7.5", 11", 14.5" and 16" Weight of entire Upper (BCG alone is just under 11oz) 4.5" is 2.59 lbs 7.5" is 2.92 lbs 11" is 3.23 lbs 14.5" is 3.57 lbs 16" is 3.72 lbs Each Bearing Delay Upper Receiver includes: Fully tunable ball bearing bolt carrier group MA Upper Receiver - slick side billet machined aluminum upper receiver MA Handguard - free float hybrid metal/polymer design MA Charging Handle - new ambidextrous design MA Muzzle Device - exclusive machined design reduces recoil and muzzle flash Also included with the purchase of the Bearing Delay Upper Receiver: 1



additional Lifter for tuning the system (2 total included) 2 Ejectorless
EndoMags (PMAGs NOT included)

Attributes

- Name: [BEARING DELAY 9MM LUGER 14.5" BBL ASSEMBLED UPPER RECEIVER](#)
- Manufacturer: [MEAN ARMS](#)
- Product no.: 430109850
- Mfr. No.: 2101969
- Cartridge: 9 mm Luger
- Color: Black
- Finish: Matte
- Length: 14.5"
- Make: AR-15
- Muzzle: 1/2-28
- Style: Complete
- Delivery weight: 2.041kg
- UPC: 855926007172

Item details

Made in USA

This product is excluded from discount promotions.

US export classification: I(g)

Table of Contents

- Startpage
- Safety Instruction Guide for Bearing Delay 9mm Luger Complete Upper Receiver
- About Us

Safety Instruction Guide for Bearing Delay 9mm Luger Complete Upper Receiver

Introduction

Thank you for choosing the Bearing Delay 9mm Luger Complete Upper Receiver. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this manual carefully and follow all safety precautions.

General Safety Guidelines

- Ensure that all safety instructions are followed to prevent accidents or injuries.
- Always treat the upper receiver as if it is loaded.
- Store the upper receiver in a secure location, out of reach of children and unauthorized users.
- Regularly inspect the upper receiver for any signs of damage or wear.
- Do not modify the upper receiver or use it in any manner not specified in this manual.
- Use only compatible ammunition to avoid malfunctions or accidents.
- Always wear appropriate safety gear, including eye protection, when using the upper receiver.

Specific Safety Precautions for Use

- Ensure that the upper receiver is properly installed on a compatible AR lower receiver before use.
- Do not use the upper receiver if it is damaged or if any components are missing.
- Always check the barrel and chamber for obstructions before firing.
- Keep your fingers away from the trigger until you are ready to shoot.
- Be aware of your target and what is beyond it when firing.
- Use the upper receiver in a safe and controlled environment, away from bystanders.

Instructions for Installation and Usage

1. Installation:

- Ensure the AR lower receiver is compatible with the Bearing Delay Upper Receiver.
- Align the upper receiver with the lower receiver and push them together until they are securely attached.
- Ensure that the takedown pins are fully engaged.
- Install the MA Charging Handle into the upper receiver.
- Attach the MA Handguard according to the provided instructions.
- Confirm that all components are properly secured.

2. Usage:

- Load the upper receiver with compatible 9mm ammunition.
- Engage the safety mechanism before loading.
- Follow standard firing procedures and maintain proper shooting stance.
- After firing, allow the upper receiver to cool before handling.
- Clean and maintain the upper receiver regularly to ensure optimal performance.

Disposal Instructions

- Dispose of the upper receiver and any associated components in accordance with local regulations.
- Do not dispose of the upper receiver in regular household waste.
- Contact local waste management authorities for proper disposal methods.

Contact Information for Further Support

For any inquiries or concerns regarding the Bearing Delay 9mm Luger Complete Upper Receiver, please refer to the manufacturer's contact details provided in the product packaging or on the official website.

Please ensure that you follow all safety guidelines and instructions provided in this manual to ensure a safe and enjoyable experience with your Bearing Delay Upper Receiver.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at