

# L89 DRIVE LOCK M-LOK RAIL - SONS OF LIBERTY GUN WORKS L89 DRIVE LOCK 13.75" M-LOK RAIL W/STEEL QD SOCKETS FOR AR15

[Rifle Parts](#) > [Build Kits](#) > [Handguards & Rails](#)

The L89 handguard takes what makes the M89 handguard a best-in-class product and elevates it even further. Featuring a Titanium barrel nut, 7 sided M-LOK attachment slots, two integrated steel QD (limited Rotation) sockets, and maximized cooling slots beneath the 12 o'clock rail, the L89 is built for end-users who require every little bit of mounting space they can get. Built on the M89/Driveloack lockup system, the L89 incorporates valued end user feedback in getting the most utility possible out of a handguard in modern combat applications. Maximum strength, maximum mounting space, and weight savings material choices make this one of the finest fighting handguards available to date. Available Lengths: 9.75" 10.75" 13.75" Finish: Mil-Spec MIL-A-8625F, Type III, Class 2, Hard Anodized Coating, Non-Reflective, NiAc Seal (Anodized to match SOLGW receivers) What's included: L89 Rail Titanium Barrel Nut Barrel Nut Wrench Lock-Up Components KEY FEATURES: 7 sided MLOK Integrated limited rotation steel QD sockets Titanium Barrel Nut Cable optimized 12 o'clock 1913 rail - cooling slots and 1913 rail slots modified for maximum cable management options



## Attributes

- Name: [SONS OF LIBERTY GUN WORKS L89 DRIVE LOCK 13.75" M-LOK RAIL W/STEEL QD SOCKETS FOR AR15](#)
- Manufacturer: [SONS OF LIBERTY GUN WORKS](#)
- Product no.: 430110643
- Mfr. No.: L89-13.75
- Colour: Black
- Length: 13.75"
- Material: Aircraft Aluminum
- Type: Tactical
- Weapon type: AR-15
- Delivery weight: 0.68kg
- Shipping height: 76mm
- Shipping width: 76mm
- Shipping length: 432mm
- UPC: 644625329285

## Item details

Made in USA  
US export classification: 0A501.y.1

# Table of Contents

- Startpage
- L89 DRIVE LOCK MLOK RAIL SAFETY INSTRUCTIONS
- About Us

# L89 DRIVE LOCK MLOK RAIL SAFETY INSTRUCTIONS

## Introduction

Thank you for choosing the L89 DRIVE LOCK MLOK RAIL from SONS OF LIBERTY GUN WORKS. This guide provides essential safety instructions, general guidelines, and proper usage to ensure a safe experience with your product. Please read all sections carefully before installation and use.

## General Safety Guidelines

- Ensure that the L89 DRIVE LOCK MLOK RAIL is installed by a qualified gunsmith or experienced individual familiar with AR15 modifications.
- Always handle firearms and firearm accessories with care and in accordance with local laws and regulations.
- Keep the product out of reach of children and unauthorized users.
- Regularly inspect the rail and its components for signs of wear or damage before each use.
- Follow all manufacturer's instructions for use and maintenance.
- If you experience any issues with the product, cease use immediately and consult a professional.

## Specific Safety Precautions for Use

### • Installation Precautions:

- Use only the provided components and tools for installation.
- Ensure all parts are securely tightened to prevent loosening during use.
- Verify compatibility with your specific AR15 model before installation.

### • Operational Precautions:

- Do not exceed the weight limit recommended for mounted accessories.
- Avoid placing any objects in the cooling slots that may obstruct airflow.
- Be aware of your surroundings and the target when using the firearm with the installed rail.

### • Maintenance Precautions:

- Clean the rail regularly to prevent debris buildup.
- Inspect the Titanium barrel nut and QD sockets for integrity before each use.
- Replace any damaged components immediately.

## Instructions for Installation and Usage

### Installation Instructions

#### 1. Preparation:

- Gather all necessary tools including the barrel nut wrench and installation components.
- Ensure your workspace is clean and welllit.

#### 2. Remove Existing Handguard:

- Unload the firearm and ensure it is safe to handle.
- Remove the existing handguard according to the manufacturer's instructions.

### **3. Install the Titanium Barrel Nut:**

- Place the Titanium barrel nut onto the barrel and tighten using the barrel nut wrench.
- Ensure it is securely fastened without overtightening.

### **4. Attach the L89 Rail:**

- Align the rail with the barrel nut and slide it into position.
- Secure the rail using the provided lockup components, ensuring a snug fit.

### **5. Install Accessories:**

- Attach any desired accessories using the 7 sided MLOK attachment slots.
- Ensure all accessories are securely mounted.

## **Usage Instructions**

- Always ensure the firearm is unloaded before making any adjustments.
- When using the firearm, maintain a firm grip and a stable shooting position.
- Regularly check the rail and accessories during use for any signs of movement or looseness.
- Follow best practices for firearm safety at all times.

## **Disposal Instructions**

- Dispose of the product in accordance with local regulations for electronic and metal waste.
- Do not dispose of the product in general household waste.
- If the product is damaged or no longer in use, ensure it is rendered unusable before disposal.

## **Contact Information for Further Support**

For any questions or concerns regarding the L89 DRIVE LOCK MLOK RAIL, please consult the manufacturer's website or contact their customer support for assistance.

## **Conclusion**

By following these safety instructions and guidelines, you can ensure a safe and effective experience with your L89 DRIVE LOCK MLOK RAIL. Thank you for your attention to safety and responsible firearm handling.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)