

# PREMIUM SLIDES FOR GLOCK® GEN 1-3 - BROWNELLS BRN PREMIUM SLIDE FOR GLOCK 43 WITH HOLOSUN 407K CUT NITRIDE

[Handgun Parts](#) > [Slide Parts](#) > [Slides](#)

MADE IN THE USA Premium Slides for Glock® 17 & 19 (Gen 1 to 4) from Brownells The Premium Slide for Glock® 17 and 19 by Brownells replaces existing non-MOS OEM slides with an upgraded look with proven patented mounting technology. Our slides feature angled serrations for better grip engagement when racking the slide rearward, pocket cuts out to reduce weight and are optic-ready. Made in the USA from quality materials, these slides are compatible from Gen 1 to Gen 4 Glock® frames. Machined from premium heat treated 17-4 Stainless Steel. Black Nitride Coating. Compatible with Gen 1, Gen 2, Gen 3, Gen 4 Glock® frames. Angled front and rear serrations. Pocket cuts for aesthetics Factory rear dovetail and front sight cut. Available with or without a top window. Premium patented ZEV Technologies optic cut with front locating bosses. The ultimate in durability and repeatability Mounting bosses are threaded 4-40 tpi Includes screws for mounting optic and shorter screws for mounting a cover plate Channel liner required for these slides. Channel liners are a press fit and require a tool to install Channel liners sold separately, 100002697, 078000649, 100024261 Channel liner tool sold separately, 777100017 ZEV Technologies. Patent No. RE47335 for optic cut technology used with licensed agreement. DISCLAIMER: "GLOCK" is a federally registered trademark of GLOCK, Inc. and is one of many trademarks owned by GLOCK, Inc. or Glock®Ges.m.b.H. Neither Brownells nor this site are affiliated in any manner with, or otherwise endorsed by, GLOCK, Inc. or Glock®Ges.m.b.H. The use of "GLOCK" on this page is merely to advertise the sale of Glock®pistols, parts, or components. For genuine GLOCK, Inc. and Glock®Ges.m.b.H. products and parts visit [www.Glock®.com](http://www.Glock®.com).

NO IMAGE  
AVAILABLE

## Attributes

- Name: [BROWNELLS BRN PREMIUM SLIDE FOR GLOCK 43 WITH HOLOSUN 407K CUT NITRIDE](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 430111190
- Mfr. No.:
- Cartridge: 9 mm Luger
- Finish: Black
- Model: 43
- Sights: Holosun 507K,Holosun 407K
- Style: Stripped
- Weapon type: Glock
- Delivery weight: 0.231kg
- UPC: 050806002098

## Item details

Made in USA

US export classification: 0A501.x

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for PREMIUM SLIDES FOR GLOCK® GEN 13](#)
- [About Us](#)

# Safety Instruction Guide for PREMIUM SLIDES FOR GLOCK® GEN 13

## Introduction

Thank you for choosing the PREMIUM SLIDES FOR GLOCK® GEN 13 from Brownells. This guide provides important safety instructions, installation guidelines, and care tips to ensure safe use of your product. Please read this document carefully to understand the proper handling and maintenance of your slide.

## General Safety Guidelines

- Ensure that the slide is compatible with your specific Glock model before installation.
- Always handle firearms and firearm components with care. Treat every firearm as if it is loaded.
- Keep the slide and all firearm components out of reach of children and unauthorized individuals.
- Inspect the slide regularly for any signs of wear or damage. Do not use if damaged.
- Follow all local laws and regulations regarding the use and modification of firearms.

## Specific Safety Precautions for Use

- Only use the slide with Glock® frames specified for compatibility (Gen 1 to Gen 4).
- Ensure the firearm is unloaded before installation or maintenance.
- Use appropriate tools for installation to avoid damaging the slide or firearm.
- If using optics, ensure they are securely mounted and compatible with the slide's optic cut.
- Be aware of the potential for sharp edges during installation and handling. Use protective gloves if necessary.
- Follow the manufacturer's guidelines for any additional components or accessories used with the slide.

## Instructions for Installation and Usage

### 1. Preparation

- Ensure you have all necessary tools, including the channel liner tool (sold separately).
- Gather the required screws for mounting optics and cover plates.

### 2. Installation Steps

- Unload your Glock® firearm and ensure it is in a safe condition.
- Remove the existing slide from the Glock® frame by following the manufacturer's instructions.
- Align the PREMIUM SLIDE with the frame, ensuring that it fits securely.
- If using a channel liner, press fit the channel liner into the slide using the appropriate tool.
- Secure the slide onto the frame, ensuring that it moves freely without obstruction.
- If applicable, mount your optic using the provided screws. Ensure that the optic is properly aligned and tightened.
- If you are not using an optic, you may install a cover plate using the shorter screws provided.

### 3. PostInstallation

- Conduct a function check to ensure that the slide operates smoothly.
- Store the firearm in a secure location, away from children and unauthorized users.

## **Disposal Instructions**

- Dispose of any damaged or worn slides and components in accordance with local regulations.
- Do not dispose of firearm components in regular household waste. Contact a local waste management facility for proper disposal methods.

## **Contact Information for Further Support**

For any questions or concerns regarding the installation or use of the PREMIUM SLIDES FOR GLOCK® GEN 13, please consult the manufacturer's website or contact their customer service for assistance.

## **Conclusion**

By following these safety instructions, you can help ensure a safe and enjoyable experience with your PREMIUM SLIDES FOR GLOCK® GEN 13. Always prioritize safety and compliance with local laws when handling firearms and their components. Thank you for your attention to these important guidelines.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)