

TACTICAL CANTILEVERED 1-PIECE SCOPE MOUNTS - TACTICAL CANTILEVER 34MM DIA 39MM HIGH 20 MOA PICATINN MOUNT

TACTICAL CANTILEVERED 1-PIECE SCOPE MOUNTS When Area 419 set out to make the perfect scope mount, they knew what they needed to make something that was reliable and consistent at a degree you won't find anywhere else on the market. This led us down a rabbit-hole, ultimately arriving on a process that gets you final-bore matched rings, with raw aluminum internals, for a grip on your optic that is more reliable and more true than anything else made – as well as an incredible amount of robustness without adding unnecessary weight. Like most mounts, these begin as separate parts. Area 419 are making the bases and caps in batches. While many will make these parts, send them to anodize, and then just assemble, they produce around the extra steps. Once these parts return from anodize, they are fully assembled, placed back into specially produced rail fixtures, with the caps torqued to spec over specially made spacers (to give the rings space to torque down on the optic), and final-bored as sets in Area 419's world-class machining centers. Mounts are then brought off the machine in sets, QC'd and packaged, ensuring that you receive a mount that was finished perfectly. Is it overkill? Probably. But Area 419 think it's the right way. So that's what they are going to do. NOTE: All 1.54" (39mm) height mounts are a more traditional AR-style cantilever. KEY FEATURES CNC Milled in America from American 7075 Aluminum Raw aluminum, precision bored scope contact surfaces for maximum grip Final-bored in sets, and never fully disassembled after boring 8-9oz per mount, depending on model, balancing weight management and robustness Multiple accessory mounting points Separate rail clamping bars for maximum grab on the pic rail Inset clamping feet, allowing for maximum mounting adjustment and pic rail utility Steel guide pins between base and caps, aiding in alignment Custom nitrided stainless hardware



Attributes

- Name: TACTICAL CANTILEVER 34MM DIA 39MM HIGH 20 MOA PICATINN MOUNT
- Manufacturer: AREA 419
- Product no.: 430112772
- Mfr. No.: 419-TCM-343920
- Elevation: 20 MOA
- Finish: Black
- Height: 6"
- Length: 2"
- Scope Tube Diameter: 34mm
- Style: Picatinny
- Delivery weight: 0.68kg
- Shipping height: 76mm
- Shipping width: 152mm
- Shipping length: 241mm
- UPC: 810080182714

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: Safety Instruction Guide for TACTICAL CANTILEVERED 1PIECE SCOPE MOUNTS](#)

Safety Instruction Guide for TACTICAL CANTILEVERED 1PIECE SCOPE MOUNTS

Introduction

Thank you for choosing the TACTICAL CANTILEVERED 1PIECE SCOPE MOUNTS. This product is designed to provide a reliable and consistent mounting solution for your optics. Please read this safety instruction guide carefully to ensure safe use and proper installation of your scope mounts.

General Safety Guidelines

- Ensure that the scope mounts are compatible with your specific optic and firearm.
- Always follow the manufacturer's instructions for the optic and firearm being used.
- Store the scope mounts in a dry and safe place, away from children and pets.
- Regularly inspect the scope mounts for any signs of wear, damage, or corrosion.
- Do not use the scope mounts if they are damaged or if any parts are missing.
- Report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Always wear appropriate eye protection when handling or installing the scope mounts.
- Ensure that the firearm is unloaded before attaching or detaching the scope mounts.
- Avoid placing excessive force on the mounts during installation, as this may lead to damage.
- Be cautious of sharp edges on the mounts and components during handling.
- If using the mounts in adverse weather conditions, ensure they are properly maintained to prevent corrosion or failure.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools, including a torque wrench, appropriate screwdrivers, and any other tools recommended by the optic manufacturer.
- Ensure that the firearm is unloaded and pointed in a safe direction.

2. Mounting the Base

- Align the scope mount base with the Picatinny rail on your firearm.
- Use the provided steel guide pins to aid in alignment.
- Secure the base using the custom nitrided stainless hardware, ensuring not to overtighten.

3. Attaching the Scope

- Place your optic onto the mounted base.
- Use the inset clamping feet to adjust the position of the optic for optimal eye relief.
- Torque the caps to the specified settings using the torque wrench.

4. Final Checks

- Ensure that all screws are tightened to the manufacturer's specifications.
- Check the alignment and stability of the mounted optic.
- Perform a visual inspection to confirm that there are no loose parts.

5. Usage

- Regularly check the mounts during usage, especially after transportation or rough handling.
- Ensure that the optic remains securely mounted during use.

Disposal Instructions

- Dispose of the scope mounts and any packaging materials in accordance with local regulations.
- If the mounts are damaged beyond repair, consider recycling the aluminum components where possible.

Contact Information for Further Support

For any inquiries regarding safety or product support, please refer to the manufacturer's contact information provided with your product packaging.

By following the guidelines and precautions outlined in this safety instruction guide, you can ensure a safe and effective experience with your TACTICAL CANTILEVERED 1PIECE SCOPE MOUNTS. Thank you for your attention to safety and for choosing our product.