

FRONT SIGHT RAMP 3/8 DOVETAIL 2-SCREW FOR REMINGTON 700 BLK

REMINGTON FRONT SIGHT RAMP 3/8 DOVETAIL 2-SCREW FOR REMINGTON 700 The Remington Front Sight Ramp 3/8" Dovetail, 2-Screw, for Remington 700 (Black) is a factory-spec replacement ramp designed to restore or upgrade the front sight interface on your Remington 700 rifle. Built from durable steel and finished in a deep black coating, this ramp provides a secure, stable mounting point for any standard 3/8" dovetail front sight blade. Its two-screw mounting pattern ensures a rock-solid installation that resists recoil shift, making it ideal for hunters, precision shooters, and anyone restoring a classic 700 to original configuration. Whether you're replacing a damaged ramp, completing a barrel project, or outfitting a rifle for iron-sight backup use, this OEM-pattern sight ramp delivers reliable alignment, consistent height, and long-term durability. **FEATURES** 3/8" Dovetail Interface — Accepts standard 3/8" dovetail front sight blades for easy customization and compatibility with common sight heights and styles. Two-Screw Mounting Pattern — Provides a secure, vibration-resistant attachment to the barrel, maintaining zero under recoil. Steel Construction — Machined from strong steel for long service life and dependable rigidity. Black Finish — Corrosion-resistant black coating blends with factory Remington 700 finishes and protects against the elements. OEM-Style Fitment — Designed for proper alignment and height on Remington 700 barrels using a front sight ramp. Ideal for Restorations or Upgrades — Perfect for bringing a rifle back to factory configuration or adding iron sights to a custom build. **NOTE:** These items are a new, authentic products acquired directly from Remington's OEM inventory. This item is guaranteed to be unused and fully functional.

NO IMAGE
AVAILABLE

Attributes

- Name: FRONT SIGHT RAMP 3/8 DOVETAIL 2-SCREW FOR REMINGTON 700 BLK
- Manufacturer: REMINGTON
- Product no.: 430116780
- Mfr. No.: F28512
- Colour: Black
- Model: 700
- Weapon type: Remington
- Delivery weight: 0.029kg

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: Safety Instruction Guide for Remington Front Sight Ramp 3/8 Dovetail 2Screw](#)

Safety Instruction Guide for Remington Front Sight Ramp 3/8 Dovetail 2Screw

Introduction

Thank you for choosing the Remington Front Sight Ramp 3/8" Dovetail, 2Screw, for Remington 700 (Black). This product is designed to enhance your shooting experience by providing a reliable front sight interface for your rifle. To ensure safe and effective use, please read this safety instruction guide carefully.

General Safety Guidelines

- Always handle firearms and firearm accessories with care and responsibility.
- Ensure that the firearm is unloaded before installing or adjusting the sight ramp.
- Store the product in a cool, dry place away from children and unauthorized users.
- Regularly inspect the sight ramp for any signs of damage or wear.
- If you experience any issues with the sight ramp, discontinue use and consult a qualified gunsmith.

Specific Safety Precautions for Use

- Ensure proper alignment of the sight ramp before securing it with screws.
- Use only compatible 3/8" dovetail front sight blades to avoid improper fit and potential hazards.
- Tighten screws to the manufacturer's specifications to maintain a secure attachment.
- Avoid using the rifle in extreme conditions that may affect the integrity of the sight ramp.
- Be aware of your surroundings and ensure a safe shooting environment when using your firearm.

Instructions for Installation and Usage

1. Preparation

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools: a screwdriver compatible with the screws provided.

2. Installation

- Locate the existing front sight ramp on your Remington 700 rifle.
- Remove the old sight ramp if applicable, taking care not to damage the barrel.
- Align the new Remington Front Sight Ramp with the dovetail slot on the barrel.
- Insert the screws into the designated holes and handtighten them.
- Use the screwdriver to securely tighten the screws, ensuring the ramp is stable and aligned.

3. Usage

- After installation, check the alignment of the front sight blade.
- Adjust the sight blade as necessary to achieve desired accuracy.
- Regularly check the tightness of the screws, especially after heavy use.

Disposal Instructions

- Dispose of packaging materials in accordance with local waste management regulations.
- If the sight ramp becomes damaged beyond repair, dispose of it responsibly by following local electronic waste disposal guidelines.

Contact Information for Further Support

For any inquiries or concerns regarding the Remington Front Sight Ramp, please consult your local Remington dealer or authorized service center.

Thank you for your attention to these safety guidelines. Your safety and satisfaction are our top priorities. Enjoy your shooting experience with the Remington Front Sight Ramp!