

PRO-HUNTER 45 CALIBER (0.4515") FLAT NOSE RIFLE BULLETS - SIERRA BULLETS, INC. PRO-HUNTER 45 CALIBER (0.4515") 260GR FLAT NOSE 100/BOX

SIERRA BULLETS, INC. PRO-HUNTER 45 CALIBER (0.4515") FLAT NOSE RIFLE BULLETS We are introducing a .4515" diameter bullet to provide an outstanding bullet weight that will be ideal in the prevalent .450 Bushmaster. Excellent feeding capability was of utmost importance along with the deepest penetration and expansion qualities combined. The flatnose allows the projectile to deliver tremendous energy transfer on game such as boar and bear. Yet deliver reliable expansion even on smaller game like coyotes. This 450 Bushmaster will be an ultimate bullet for deer as well. SPECS Bullet Type: Flatnose (FN) Purpose: Hunting Pursuit: Big Game Bullet Material: Jacketed Lead



Attributes

- Name: SIERRA BULLETS, INC. PRO-HUNTER 45 CALIBER (0.4515") 260GR FLAT NOSE 100/BOX
- Manufacturer: SIERRA BULLETS, INC.
- Product no.: 430117119
- Mfr. No.: 8760
- Ballistic Coefficient (G1): 0.164
- Brand Style: Pro-Hunter
- Bullet Style: Flat Nose (FN)
- Caliber: 45 Caliber
- Diameter (Breech): 0.4515
- Diameter (in): 0.4515
- Grain: 260
- Quantity: 100
- Delivery weight: 1.724kg
- Shipping height: 66mm
- Shipping width: 56mm
- Shipping length: 91mm

Item details

Made in USA

US export classification: 0A505.x

Table of Contents

- [Startpage](#)
- [English: PROHUNTER 45 CALIBER FLAT NOSE RIFLE BULLETS SAFETY INSTRUCTIONS](#)

PROHUNTER 45 CALIBER FLAT NOSE RIFLE BULLETS SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the PROHUNTER 45 Caliber (0.4515") Flat Nose Rifle Bullets from Sierra Bullets, Inc. This guide provides essential safety instructions to ensure the proper and safe use of this product. Please read this manual thoroughly before using the bullets.

General Safety Guidelines

- Always treat every bullet as if it is loaded and ready to fire.
- Store bullets in a cool, dry place away from direct sunlight and moisture.
- Keep bullets out of reach of children and unauthorized individuals.
- Always use appropriate protective gear, including eye and ear protection, when handling or shooting.
- Ensure your firearm is in good working condition and suitable for the caliber of bullets you are using.
- Follow all local laws and regulations regarding the purchase, storage, and use of ammunition.

Specific Safety Precautions for Use

- Only use these bullets in firearms specifically chambered for .450 Bushmaster.
- Do not attempt to modify or alter the bullets in any way.
- Check the bullet's condition before use; do not use damaged or corroded bullets.
- Avoid using these bullets in firearms that are not designed for highpressure loads.
- Be aware of your surroundings and ensure a safe shooting environment.
- Always follow the manufacturer's instructions for your firearm regarding ammunition.

Instructions for Installation and Usage

- Ensure the firearm is unloaded before handling bullets.
- Clean your firearm's chamber and barrel before loading new ammunition.
- Load bullets according to the firearm manufacturer's guidelines, ensuring they are seated properly.
- When ready to shoot, ensure the safety is engaged until you are prepared to fire.
- Always aim in a safe direction and be aware of your target and what lies beyond it.
- After shooting, inspect the firearm for any signs of malfunction before reloading.

Disposal Instructions

- Dispose of any unused or damaged bullets in accordance with local regulations.
- Do not discard bullets in regular household waste.
- Contact your local law enforcement agency or hazardous waste disposal facility for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the PROHUNTER 45 Caliber Flat Nose Rifle Bullets, please reach out to the appropriate safety authorities or consult the manufacturer's website for further assistance.

By following these guidelines, you can help ensure a safe and enjoyable shooting experience. Always prioritize safety and be responsible when handling firearms and ammunition.